Evaluation Carrier Board for SMARC Module conga-SEVAL





Evaluation Carrier Board

compatible with SMARC modules

Ethernet

2x Gigabit Ethernet

Internal connectors

1x PCle x4 | 1x miniPCle | 1x PCle x1 | 1x M.2 socket Key E

x SATA

1x USB 3.0 | 1x USB 2.0 | 1x micro USB 2.0 (OTG) | 1x USB Type C with PD and DP1 via Alternate Mode

2x RS-232 (1x internal RX/TX on pinheader, 1x RX/TX w/ handshake on DSUB9)

2x CAN GPIO

1x SDIO interface

2x I²C Bus

1x eSPI/SPI1 on header

1x eSPI/SP 1x SPI Bus

1x FAN control

1x Disk Drive Power Output

Internal Graphic Interface

2x24 bit LVDS connector shared with 2x eDP or 2xDSI

External Graphic Interfaces

1x DP++ 1x HDMI

Camera Interface

Audio

I2S Audio interface and HDA interface

Buttons and LED's

Power button | Reset button | Sleep button | LID button | various indication LEDs

Feature Connector

1x Standard congatec Feature Connector

Postcode Temperature 4x 7-Segment Postcode LEDs connected to GP_I2C bus
Operating: -40 .. +85°C | Storage: -20 .. +80°C

Power Input

ATX Power Supply | 12V - 24V Wide Range Carrier Board Supply | 3.0V - 5.25V Wide Range Module Supply | USB Type C PD (12V - 20V)

Humidity

Operating: 10 - 90% r. H. non cond. | Storage: 5 - 95% r. H. non cond.

294 x 172 mm

conga-SEVAL | Order Information

Article

PN

Descriptio

conga-SEVAL

007010

Evaluation Carrier Board for SMARC 2.0 modules



Gefördert durch:



aufgrund eines Beschlusses des Deutschen Bundestages

© 2021 congatec GmbH. All rights reserved. All data is for information purposes only. Although all the information contained within this document is carefully checked, no guarantee of correctness is implied or expressed. Product names, logos, brands, and other trademarks featured or referred are the property of their respective trademark holders. These trademark holders are not affiliated with congatec GmbH. Rev. Jan 22, 2021 KF

